# Zeiss LSM 980



## Startup

- 1. Turn the Main Switch (1) in ON position
- 2. Turn the Laser key (2) clockwise in vertical position (labeled "Laser")
- 3. Push the Components switch (3) in ON position
- 4. Power up the PC (4). Login into the "user" account and start ZEN
- 5. Press the Load position button on the touch panel of the microscope



Home	Objective: Resolution: Optovar:	63x/0.75 Ph2 0.44 µm	Load
ficroscope	Tot mag :	630x 💭	position TL Illumination
Settings	VIS:	43 HE DsRed BF NA=0.09 50%	Off On RL Illumination
	Sideport: Baseport: Frontport:	77.V2.7-03	Off On
Display	Z-Position: X-Position: Y-Position: Fieldstop RL:	1.753 mm	Make It Visible1

# Zeiss LSM 980



### Shutdown

- 1. Close ZEN
- 2. Press the Load position button on the touch panel
- 3. Clean immersion objectives with lens cleaning paper

### a. Leaving the system for the next user

4. Logout from the Windows session

### b. Full shutdown (last user)

- 4. Shut down the PC (4)
- 5. Push the Components switch (3) in OFF position
- 6. Turn the Laser key (2) counter-clockwise in horizontal position (labeled "OFF")
- 7. Turn the Main Switch (1) in OFF position
- 8. Cover the microscope with the dust cover